## 2007 Dodge Nitro R/T

2007 ACCESSORIES AND EQUIPMENT Overhead Console - Service Information - Nitro

## 2007 ACCESSORIES AND EQUIPMENT

**Overhead Console - Service Information - Nitro** 

# OVERHEAD CONSOLE-SERVICE INFORMATION

### **DESCRIPTION**

#### OVERHEAD CONSOLE





Fig. 1: Identifying Overhead Console, Sunroof Switch, Courtesy Lamps & Infrared Temperature Sensor Courtesy of CHRYSLER LLC

An overhead console (1) is standard factory-installed equipment on this model. All overhead consoles are equipped with two reading and courtesy lamps (3). On vehicles equipped with a power sunroof, the sunroof switch (2) is located between the two reading and courtesy lamps. On vehicles equipped with automatic climate control an infrared temperature sensor (4) is located on the front edge of the overhead console. The overhead console is mounted with three snap clips into a molded plastic retainer bracket located above the headliner to provide secure overhead console attachment.


### **REMOVAL**

**OVERHEAD CONSOLE** 



<u>Fig. 2: Identifying Overhead Console, Sunroof Switch, Courtesy Lamps & Infrared Temperature Sensor</u> Courtesy of CHRYSLER LLC

- 1. Disconnect and isolate the battery negative cable.
- 2. Using your fingertips, grasp the sides of the overhead console (1) and pull straight down evenly to disengage the three snap clips from the mounting bracket.



<u>Fig. 3: Identifying Overhead Console & Wire Harness Connector</u> Courtesy of CHRYSLER LLC

- 3. Lower the overhead console (1) far enough to access the wire harness connector (2).
- 4. If equipped, disconnect the courtesy lamps, infrared temperature sensor and power sunroof switch electrical connectors.
- 5. Remove the overhead console (1) assembly from the vehicle.

### INSTALLATION

## 2007 Dodge Nitro R/T

2007 ACCESSORIES AND EQUIPMENT Overhead Console - Service Information - Nitro

#### **OVERHEAD CONSOLE**





Fig. 4: Identifying Overhead Console & Wire Harness Connector Courtesy of CHRYSLER LLC

- 1. Position the overhead console (1) in the vehicle near the headliner assembly.
- 2. If equipped, connect the courtesy lamps, infrared temperature sensor and power sunroof switch electrical connectors (2).



<u>Fig. 5: Identifying Snap Clips & Overhead Console</u> Courtesy of CHRYSLER LLC

- 3. Grasp the sides of the overhead console (2) and push straight up evenly to engage the three snap clips (1) into the mounting bracket.
- 4. Connect the battery negative cable.